

MIU/POWERPORT Low Voltage, DC Powered Modems

1.2, 2.4, 9.6, 14.4 & 28.8 kbps

KEY FEATURES

- Bell 202T, V.22bis, V.32bis, V.34
- Dial-Up and Leased Lines
- Powered from -5 to -24VDC through the DB25 Data Port or an External Jack
- Automatic "Power Down" when inactive
- -40°C to +85°C Operating Temperature
- Hayes AT Compatible
- Ideal for Meters, Relays, RTUs, Controllers, etc.

The **Raymar-Telenetics** MIU/PowerPort can be powered by delivering +5VDC (regulated) through pin 10 or the DB25. An optional -7 to -16VDC version is also available. Alternatively, an external jack allows the MIU/PowerPort to be powered from a wall transformer or other low voltage AC or DC power source.

When not online, the dial-up MIU/PowerPort modems automatically goes into a power down mode and consumes only a few microamps while inactive.

The MIU/PowerPort operates over dial-up and 2-wire/4-wire leased lines at full or half duplex as appropriate with various modulations, including:

» Bell 202T	(1200bps)
» V.22bis	(2400bps)
» V.32bis	(14400bps)
» V.34	(288000bps)

The MIU/PowerPort is fully Hayes™ AT command set compatible with programmable S-registers.

All models will operate in temperatures from -40°C to +85°C and are surge protected on the analog line up to 5kV.



The MIU/PowerPort is an industrial grade modem that is designed to be powered directly through the RS232 (DB25) data interface port.

RAYMAR INFORMATION TECHNOLOGY, INC.

7325 Roseville Road
Sacramento, CA 95842
USA

+1-916-783-1951

FAX +1-916-783-1952

sales@raymarinc.com

1-800-695-1951

Tech Support Hotline
1-800-747-1522

www.raymarinc.com

MIU/POWERPORT • Low Voltage, DC Powered Modems

TECHNICAL SPECIFICATIONS

	MIU/PowerPort 202T	MIU/PowerPort 9.6 & 9.6L	MIU/PowerPort 14.4 & 14.4L	MIU/PowerPort 28.8
Modem Line Speeds: Asynchronous	0 - 1200bps	2400, 1200, 300bps	14400, 9600, 4800, 2400, 1200, 300bps	28800, 14400, 9600, 4800, 2400, 1200, 300bps
DTE Rates: above modem line speeds (ie; with data compression)	—	19200, 9600, 4800bps	57.6, 38.4, 19.2kps	115.2, 57.6, 38.4, 19.2kps
Standards:	Bell 202T	V.22bis, V.22 Bell 212A Bell 103	V.32bis, V.32 V.22bis, V.22 Bell 212A, Bell 103	V.34, V.32bis, V.32 V.22bis, V.22 Bell 212A, Bell 103
Dial Up	No	Yes (Model 9.6)	Yes (Model 14.4)	Yes
2 / 4-W Leased Line	Yes ¹	Yes (Model 9.6L ²)	Yes (Model 14.4L ²)	No
Configuration	Dip Switch	Hayes™ Extended AT Command Set		
Error Correction/ Data Compression	None	MNP 2, 4, 5 & 10 V.42, V.42bis		
Power Requirement	+5VDC ±5% in through Pin 10 on the DB 25 Data Port (Option: -7 to -16VDC in through Pin 10 on the DB25 Data Port. Please Specify) The modem can also be powered from an optional 120VAC wall transformer.			
Current Consumption	128mA @ +5VDC 71mA @ 12VDC	100mA @ +5VDC 56mA @ 12VDC	219mA @ +5VDC 123mA @ 12VDC	287mA @ +5VDC 160mA @ 12VDC
Digital Port	RS232 with DB25 Female Connector			
Analog Port	RJ-11 Modular Jack			
Surge Protection (Analog Port)	3.75kVac	5kVac	3.75kVac	3.75kVac
Environment	-40°C to +85°C, 0 to 95% humidity (non-condensing)			
Case Size	5-3/8" x 4" x 1-3/8"			
Certifications	FCC Part 68 Class A; Industry Canada Certified			

Important Notes regarding leased line operation:

¹ Bell202T is half or full duplex, suitable for point-to-point and multipoint applications.

² The standard 9.6L and 14.4L models are 4-wire, full or half duplex, point-to-point only. 2-wire, full duplex, point-to-point available on special order.

WARRANTY

Raymar-Telenetics manufactured products are warranted against defects in hardware material and workmanship under normal use for one (1) year from date of original retail purchase. Defective product will be repaired or replaced, determination to be made by Raymar-Telenetics, at no charge. Repaired or replaced products are warranted for 90 days or for original warranty period, whichever is longer. Warranty extends to original end-user only.



Manufactured in the USA by RAYMAR-TELENETICS

Raymar Information Technology, Inc., 7325 Roseville Road, Sacramento, CA 95842
1-800-695-1951 fax +1-916-783-1952 sales@raymarinc.com www.raymarinc.com
Service Support Hotline 1-800-747-1522